


**Multipair Individually Screened Cables-
Belden Equivalent 9876**



Applications	These cables have individually screened pairs laid up. Each individually screened pair has a 22AWG stranded tinned copper drain wire. These cables are used as computer cables.
Construction	
Conductor	Tinned copper wire.
Insulation	PP
Individual Screen	Aluminium/Polyester tape.
Drain Wire	Tinned copper wire.
Sheath	PVC (V type)/LSZH (H type).
Insulation Colour	Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown, Black & Orange, Red & White, Red & Green, Red & Blue, Red & Yellow.

Electrical & Mechanical Characteristics

AWG		20
Conductor Construction		7x0.32
UL Style		2919
Maximum Conductor Resistance	Ω/km	34.1
Voltage Rating	V	30
Nominal Capacitance Conductor to Conductor	pF/m	98
Nominal Capacitance Conductor to Screen	pF/m	180
Bending Radius		10xOverall Diameter
Operating Temperature	°C	-20~80

Dimensions

Part No.	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
----------	--------------	----------------------	------------------	------------------

		mm	mm	mm
UEBE 9876V	11	0.33	1.22	15.2
UEBE 9876H	11	0.33	1.22	15.2