


Foundation Fieldbus ISA/SP-50 High Speed



Application:

Foundation™ Field bus is used in intrinsically area, especially in the field of Process Automation. A high speed single pair 22AWG Bi-Directional digital Fieldbus cable for 1.0 & 2.5MBit/sec applications available in PVC, LSHF and SWA versions. Anti-termite and anti-vermin foundation fieldbus cable is also available.

Construction:

Type	Foundation Fieldbus ISA/SP-50 High Speed
Inner Conductor	Tinned copper conductors 22(7)AWG 0.34mm ²
Conductor Insulation	Foamed polyolefin
Stranding Element	-
Shielding	Aluminium /polyester foil
Drain Wire	(22AWG) tinned copper
Outer Jacket Material	PVC
Core Identification	White & Black
Sheath Colour	Orange

Electrical Data:

Characteristic Impedance@1MHz	150 Ω±10 Ω
Conductor resistance	56.0 Ohm/km @ 20°C
Working Voltage	300V
Test Voltage	1.5KV
Attenuation	39kHz < 3 dB/100m

Technical Data:

Weight:	approximately 65 kg/km/ 287 kg/km(SWA)
----------------	--

Min. Bending Radius (Laying)	15 x OD mm
Operating Temp.Range, min.	- 25 °C
Operating Temp.Range, max.	+80 °C
