



American Standard UL Industrial Cables TW

Application and Description The TW conductor is suitable for most current wiring solutions for residential, commercial and industrial environments. It is used in branch circuits for permanent installations. TW conductors in sizes 14 AWG to 8 AWG can be installed in conduits and other raceways. The temperature of installation shall not exceed 60°C.

Cable Construction

Conductor	Bare annealed copper conductor, solid or stranded
------------------	---

Insulation	PVC 60°C insulation
-------------------	---------------------

Color	upon request, black is preferable
--------------	-----------------------------------

Technical Compliances	<ul style="list-style-type: none"> - ASTM B3, B8 - UL 83 - Thermoplastic-Insulated Wires and Cables - UL 1581 - Electrical Wires, Cables and Flexible Cords
------------------------------	--

Cable Parameter

AWG or kcmil	Strand	Nominal Insulation Thickness Inch/mm		Nominal Overall Diameter Inch/mm		Cable Weight	
		Lbs/kft	kg/km	Lbs/kft	kg/km	Lbs/kft	kg/km
14	1	0.030	0.76	0.138	3.5	19	28
12	1	0.030	0.76	0.154	3.9	27	40
10	1	0.030	0.76	0.177	4.5	40	60
8	1	0.045	1.14	0.240	6.1	67	100
14	7	0.030	0.76	0.146	3.7	19	29
12	7	0.030	0.76	0.165	4.2	29	43
10	7	0.030	0.76	0.193	4.9	44	65
8	7	0.045	1.14	0.260	6.6	72	107