

P2 or P2/P9 RFOU/TFOU 3.6/6KV



- Armour
- Conductors
- Conductor Screen
- Insulation Screen
- Insulation
- Inner Sheath
- Outer Sheath

Applications :	These cables are flame retardant, low smoke, halogen free and mud resistant, used for fixed installation for medium voltage power.
Standards :	IEC 60092-353; IEC 60092-351; IEC 60092-359; IEC 60332-1; IEC 60332-3-22; IEC 60754-1,2; IEC 61034-1,2; NEK 606:2004
Conductors :	Circular tinned annealed stranded copper to IEC 60228 class 2.
Conductor Screen :	Semi conducting material.
Insulation :	Halogen-free EPR. XLPE can be offered as an option (for TFOU cable).
Insulation Screen :	Semi conducting material and tinned copper wire braid.
Bedding :	Halogen free compound.
Armour :	Tinned copper wire braid.
Outer Sheath :	Halogen free thermosetting compound, SHF2 (for TYPE P2), or halogen free mud resistant thermosetting compound, SHF MUD (for TYPE P2/P9),coloured red.

Electrical Characteristics :

Nominal Cross Section Area	mm ²	16	25	35	50	70	95	120
Nominal Conductor Diameter	mm	5.1	6.5	7.4	8.7	10.3	12.2	13.8
Maximum DC Resistant@20°C	Ω/km	1.16	0.734	0.529	0.391	0.27	0.195	0.154
Continuous Current Rating@45°C1 Core	A	96	127	157	196	242	293	339
Continuous Current Rating@45°C3 Core	A	67	89	110	137	169	205	237
Short Circuit Current 1s	A	2290	3580	5010	7150	10020	13590	17170
Operating Voltage	KV	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6
Nominal Cross Section Area	mm ²	150	185	240	300	400	500	630
Nominal Conductor Diameter	mm	15.1	17.0	19.6	21.9	24.6	27.6	32.5
Maximum DC Resistant@20°C	Ω/km	0.126	0.1	0.0762	0.0607	0.0475	0.0369	0.0286

Continuous Current Rating@45°C1 Core	A	389	444	522	601	690	780	890
Continuous Current Rating@45°C3 Core	A	272	311	365	421	483	546	623
Short Circuit Current 1s	A	21460	26470	34340	42930	57230	71540	90140
Operating Voltage	KV	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6	3.6/6

Ambient Temperature Correction Factors :

Ambient Temperature Correction Factors	35	40	45	50	55	60	65	70	75	80
Rating Factor	1.1	1.05	1.0	0.94	0.88	0.82	0.74	0.67	0.58	0.47

Mechanical and Thermal Properties :

Bending Radius :15×OD (during installation); 9×OD (fixed installed).

Temperature Range : -20°C ~ +90°C.

Dimensions and Weight :

Construction No. of cores×Cross section (mm²)	Nominal Insulation Thickness mm	Nominal Sheath Thickness mm		Nominal Overall Diameter mm	Nominal Weight kg/km
		Inner	Outer		
1×16	2.5	1.4	1.1	22.8	780
1×25	2.5	1.5	1.1	24.0	1020
1×35	2.5	1.5	1.2	25.1	1155
1×50	2.5	1.6	1.2	26.3	1320
1×70	2.5	1.6	1.3	28.2	1595
1×95	2.5	1.7	1.3	30.0	1905
1×120	2.5	1.8	1.4	31.8	2235
1×150	2.5	1.8	1.4	33.5	2550
1×185	2.5	1.9	1.5	35.4	3015
1×240	2.6	2.0	1.5	38.8	3725
1×300	2.8	2.1	1.6	42.3	4625
1×400	3.0	2.2	1.7	46.6	5420
1×500	3.2	2.4	1.8	50.8	6610
1×630	3.2	2.5	1.9	55.1	8170
3×16	2.5	2.2	1.6	44.9	2930
3×25	2.5	2.3	1.7	45.4	3390
3×35	2.5	2.4	1.8	47.6	3820
3×50	2.5	2.5	1.9	50.9	4495
3×70	2.5	2.7	2.0	54.8	5585

3×95	2.5	2.8	2.1	58.9	6765
3×120	2.5	3.0	2.2	63.5	8165
3×150	2.5	3.1	2.3	67.4	9495
3×185	2.5	3.3	2.4	75.8	10660
3×240	2.6	3.5	2.5	82.3	11660
3×300	2.8	3.8	2.7	89.3	12940