

EB

E: Grounding B: Bond

Application

For internal wiring of vehicles metres circuits and electronic equipments where exposed to temperatures not Exceeding 80°C.

Standards/Specification

JASO D611-09



Construction

- ① Conductor: Stranded, bare copper
- ② Insulation: PVC

Product Features

Rated temperature: -40°C to 80°C

Rated voltage: 25 VAC and 60 VDC

Technical Data

No.	Conductors			Conductors Resistance (Ω/km)	Insulation		Overall Diameter	
	Nominal Size (mm ²)	Construction (No./mm)	Outer Diameter (mm)		Std. Thick. (mm)	Min. Thick (mm)	Standard (mm)	Max (mm)
5	7/9/0.32	5.067	3.1	3.71	0.60	0.48	4.3	4.7
9	7/16/0.32	9.008	4.2	2.09	0.60	0.48	5.4	5.8
10	19/6/0.32	9.168	4.2	2.05	0.60	0.48	5.5	5.9
15	19/9/0.32	13.75	5.3	1.37	0.60	0.48	6.5	6.9
20	19/13/0.32	19.86	6.5	0.946	0.60	0.48	7.7	8.1
30	19/19/0.32	29.03	7.8	0.647	0.60	0.48	9.0	9.4
40	19/26/0.32	39.73	9.1	0.473	0.60	0.48	10.3	10.8
50	19/32/0.32	48.90	10.1	0.384	0.60	0.48	11.3	11.9
60	19/39/0.32	59.59	11.1	0.315	0.60	0.48	12.3	12.9
85	19/56/0.32	85.57	13.1	0.220	0.60	0.48	14.3	15.0