


Foundation Fieldbus ISA/SP-50 Profibus PA Type A



Application:

Foundation™ Field bus is used in intrinsically area, especially in the field of Process Automation. A single pair 18AWG Bi-Directional digital Fieldbus cable for type A applications (31.25 KBits/sec) available in PVC, LSHF and SWA versions. Anti-termite and anti-vermin foundation fieldbus cable is also available.

Construction:

Type	Foundation Fieldbus ISA/SP-50 Profibus PA Type A
Inner Conductor	Tinned copper conductors 18(7)AWG 0.88mm ²
Conductor Insulation	Polyolefin/Foamed PE with skin PE
Stranding Element	-
Shielding	Aluminium /polyester foil
Drain Wire	(20AWG) tinned copper
Outer Jacket Material	PVC
Core Identification	White & Black
Sheath Colour	Orange

Electrical Data:

Characteristic Impedance@31.25KHz	100 Ω±20 Ω
Conductor resistance	24 Ohm/km @ 20°C
Working Voltage	Max: 300V
Test Voltage	1.5KV
Nominal attenuation	39kHz < 3dB/km

Technical Data:

Weight:	approximately 85 kg/km/ 246 kg/km(SWA)
----------------	--

Min. Bending Radius (Laying)	15 x OD mm
Operating Temp.Range, min.	- 25 °C
Operating Temp.Range, max.	+80 °C